





CUSTOMER DATA SHEET	CDS No: J5200000	Status: On Sale
Product: JACKSON SAFETY AIRMAX R60		Date: Mar 2011
Power Assisted Purifying Respirator (PAPR) TH2P R SL		Version: 2
Countries sold into: EMEA		Replaces: V1. Feb 2010

FINISHED PRODUCT

Property	Typical Values
Regulatory compliance	DIN EN 12941: 2009
Nominal Protection Factor (NFP)	50
Respiratory classification	TH2P R SL
Total Inward leakage @ 95±2 LPM, NaCl and Parafin oil mist	< 2%
Inhalation Resistance	Power on state: < 0.5%
Resistance to clogging	Power off state: < 1%
Noise generation (blower unit)	< 7mBar
Product appearance	Inhalation resistance: <11mBar (OFF), <3.5mBar (ON)
	Exhalation not to exceed 7mBa
	Typical: 62dB (max 75dB allowed)
	Compliance CE marks
	Head tops:
	
	Blower unit:
	
	
R60 AIRMAX* blower unit	
Net product weight:	About 930gr. Includes blower + filter+ battery pack
Component Specifications	Fiberglass folded paper in a ABS housing
1. Reusable	
R SL filter: Filtration area: 3475cm ²	
Reusable protection against <i>solid</i> and <i>liquid</i> airborne particles	
2. Blower unit	Combination of stainless steel and synthetic materials
	Min flow rate: 170LPM (typical 200LPM)
	ABS and flame resistant Proban* material
3. Face seal, hose and hose cover	Strength of coupling to hood: Tested and passed at 100N
	Nylon covered with flame resistant Proban* material
4. Waist belt	Li-Ion type
5. Battery	Compliant with EU Electromagnetic Compatibility and Low Voltage Directives
6. Charger	Specifications: 7.4V, 1.3A.
	Free of silicone and latex
7. All materials	Enclosed, in applicable global languages
Instructions for use:	

PACKAGING

Blower unit:	Components:
	<ol style="list-style-type: none"> 1. Blower unit – motor (not sold as a spare part) 2. J5220 PAPR battery pack 3. J5230 PAPR charger 4. J5210 PAPR R SL filter 5. J5242 PAR blower waist belt 6. J5240 PAPR hose 7. J5241 PAPR hose cover
	Case count: 1 complete unit per case Case size LxWxH: 380x240x140 mm (ID) Gross weight/case: 1.5Kg Net weight/case: 1.3 Kg

CUSTOMER DATA SHEET	CDS No: J5200000	Status: On Sale
Product: JACKSON SAFETY AIRMAX R60		Date: Mar 2011
Power Assisted Purifying Respirator (PAPR) TH2P R SL		Version: 2
Countries sold into: EMEA		Replaces: V1. Feb 2010

Head Top combinations:

R60 AIRMAX* PAPR system to be used with approved WH30 Albatross, WH40 Element and WH50 Multiview head tops to provide added respiratory protection during a wide range of grinding and/welding applications.

A few head tops are shown below. Consult KCP Safety Welding PPE catalogue for further details on the wider range of PAPR head top options available to work with the R60 AIRMAX* PAPR blower unit.

		
J5033. WH30 Albatross PAPR head top Ideal for extended respiratory protection during professional welding/torch cutting and grinding tasks.	J5020. WH40 Element PAPR head top Ideal for extended respiratory protection during professional welding tasks.	J5022. WH50 Multiview PAPR head top Ideal for extended respiratory protection during professional welding tasks where increased awareness from a wider viewing area is needed

Features	Benefits
<ul style="list-style-type: none"> Great value with multiple head top combinations Improved safety features Flame resistant materials Adjustable waist belt Safe and user friendly charger Full serviceability Various main adaptors Rechargeable battery KCP Warranty 	<ul style="list-style-type: none"> Excellent performance/weight for increased respiratory protection in welding related environments Minimum flow rate visual and audible failure mode Exclusive bayonet coupling to ensure correct connection of Jackson Safety* exclusive components and spare parts Built-in ON/OFF switch to avoid the unit accidentally turning off while in use TH2P R SL filter with built in spark deflector For increased life of materials exposed to heat, flame and molten solids For easy adjustment to any waist size Short circuit protected, multiple quick release mains power sockets Wide range of spare parts available for extended system lifetime, contact KCP for details For use in EU/UK/RofW/AS/NZ Battery will last at least 6 hours and can be recharged overnight for the following shift. Please follow the instructions for use provided with the product R60 AIRMAX* PAPR blower unit supplied with 1.5 year limited manufacturer warranty. Conditions apply, please read the terms and conditions on the KCP Jackson Safety* catalogue or contact KCP for details: www.kcprofessional.com/uk

IMPORTANT NOTICE

This data was generated from samples which were taken to be typical of standard product. The data is given for information only. Always review the instructions provided with each PPE device before use. These specifications and information contained herein are the property of Kimberly-Clark. Copies, like the originals, are considered as trade secrets.